

## § 421.144

achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable:

(a) Sodium Antimonate Autoclave Wastewater.

### BAT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony contained in sodium antimonate product	
Antimony .....	30.150	13.440
Arsenic .....	21.720	9.687
Mercury .....	2.344	0.937

(b) Fouled Anolyte.

### BAT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg pounds per million pounds of antimony metal produced by electrowinning	
Antimony .....	30.150	13.440
Arsenic .....	21.720	9.687
Mercury .....	2.344	0.937

(c) Cathode Antimony Wash Water

### BAT LIMITATIONS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant of pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony metal produced by electrowinning	
Antimony .....	60.310	26.870
Arsenic .....	43.430	19.370
Mercury .....	4.687	1.875

## § 421.144 Standards of performance for new sources.

Any new source subject to this subpart shall achieve the following new source performance standards:

(a) Sodium Antimonate Autoclave Wastewater.

## 40 CFR Ch. I (7–1–09 Edition)

### NSPS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony contained in sodium antimonate product	
Antimony .....	30.150	13.440
Arsenic .....	21.720	9.687
Mercury .....	2.344	0.937
Total suspended solids .....	234.400	187.500
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(b) Fouled Anolyte.

### NSPS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony metal produced by electrowinning	
Antimony .....	30.150	13.440
Arsenic .....	21.720	9.687
Mercury .....	2.344	0.937
Total suspended solids .....	234.400	187.500
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

(c) Cathode Antimony Wash Water.

### NSPS FOR THE PRIMARY ANTIMONY SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of antimony metal produced by electrowinning	
Antimony .....	60.310	26.870
Arsenic .....	43.430	19.370
Mercury .....	4.687	1.875
Total suspended solids .....	468.700	375.000
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range of 7.5 to 10.0 at all times.

## § 421.145 [Reserved]

## § 421.146 Pretreatment standards for new sources.

Except as provided in 40 CFR 403.7, any new source subject to this subpart which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment